

USB/PCIe/PXIe-5710 Series

Family of Analog Output Modules



🔗 Please download JYTEK <[JYPEDIA](#)>, you can quickly inquire the product prices, the key features and available accessories.

Overview

The USB/PCIe/PXIe-5710 Series is a family of Analog Output function modules, which can run on PCIe, PXIe, TXI (Thunderbolt) and USB buses. Depending on the model number, a 5710 series provide different AO channels, sampling rate.

JYTEK PCIe/PXIe-5711 is a 32 channels analog output module with 16 bits resolution. PCIe/PXIe-5711 has an output range of ± 10 V with maximum update rate to 2 MS/s. It also provides output current drive in the range of ± 10 mA.

USB-5710 Series supports USB 3.0 bus protocol or above.

Main Features

- 32 channels of voltage output
- 16 bits DAC
- Output range: ± 10 V
- Maximum update rate
 - 1 channel.....2 MS/s
 - 8 channels (1 channel per bank).....2 MS/s
 - 32 channels.....1 MS/s
- Output current drive: ± 10 mA
- Overdrive current: 15 mA
- 8M samples FIFO buffer size per channel
- DMA for data transfers

Hardware Specifications

Analog Output Specifications

Number of channels	32 ch
Resolution	16 bits
DNL	±1 LSB
Unscaled data format	Signed integer (-32768 to 32767)
Monotonicity	16 bits
Clock	200 MHz
Maximum update rate	
1 channel	2 MS/s
8 channels (1 channel per bank)*	2 MS/s
32 channels	1 MS/s
Output range	±10 V
Output coupling	DC
Output impedance	0.2 Ω
Output current drive	±10 mA
Overdrive protection	±15 V
Overdrive current	15 mA
Power-on state	±200 mV
FIFO buffer size	8M Samples per channel
Data transfers	DMA
AO waveform modes	Nonperiodic waveform, Periodic waveform regeneration mode from onboard FIFO, Periodic waveform regeneration from host buffer including dynamic update
Slew rate	20 V/μs
Noise	400 μVrms, DC to 1 MHz
AO update glitch Glitch energy	5 nVs
Channel crosstalk	-65 dB
Reference clock	PXIe_DSTARA, PXIe_DSTARB, PXIe_CLK100
External sample clock	PFI, PXI_TRIG
Trigger source	Digital, Software
Trigger type	Start Trigger
Digital trigger source	PFI, PXI_TRIG
* Each bank consists of four AO channels using two DACs. Any channels being used within a single bank will update simultaneously.	

* Each bank consists of four AO channels using two DACs. Any channels being used within a single bank will update simultaneously.

Analog Output Specifications

JY5711 AO Basic Accuracy = \pm (% of Output+% of Range)								
Nominal Range (V)	24 Hour Tcal $\pm 1^{\circ}$		90 Days Tcal $\pm 5^{\circ}$		24 Hr Full-Scale Accuracy	90 Days Full-Scale Accuracy		
10	0.003	+	0.005	0.012	+	0.008	790 μ V	2000 μ V

JY5711 AO Additional Accuracy Adjustment				
Nominal Range (V)	Temperature Coefficients (/ $^{\circ}$ C)		Full-Scale Temp Adjustment (μ V/ $^{\circ}$ C)	
10	0.0007	+	0.0002	90 μ V

Digital IO Specifications

Static Characteristics

Number of channels	3 DIO
Ground reference	DGND
Direction control	Each terminal individually programmable as input or output
Pull-down resistor	50 k Ω typical
Input voltage protection	± 15 V

PFI Specifications

Number of channels	3
External digital trigger interface	Trigger voltage 3.3 V TTL; Trigger edge: Rising/Falling
Initial state	Input

Power Requirements

3.3 V:	3.0 W
+12 V:	14.0 W

Physical and Environment

Operating Environment

Ambient temperature range	0 $^{\circ}$ C to 50 $^{\circ}$ C
Relative humidity range	20% to 80%, noncondensing


Storage Environment

Ambient temperature range	-20 °C to 80 °C
Relative humidity range	10% to 90%, noncondensing

Performance and Tests

AO Accuracy

JY5711 AO Basic Accuracy = $\pm(\% \text{ of Output} + \% \text{ of Range})$						
Nominal Range (V)	24 Hour Tcal $\pm 1\text{C}^\circ$		90 Days Tcal $\pm 5^\circ$		24 Hr Full-Scale Accuracy	90 Days Full-Scale Accuracy
10	0.003	+ 0.005	0.007	+ 0.011	790 μV	1800 μV



Crosstalk

Reference Channel	Tested Channel	Crosstalk (dB at 100 KHz)
0	1	-71.8
0	15	-71.4
0	16	-70.4
1	2	-71.8
6	7	-71.4
6	22	-70.9
10	11	-72.1
16	17	-67.2
31	30	-71.6

Order Information

- PXIe-5711 (PN: JY5711001-01)
32-ch, 2MS/s/ch, 16-bit PXIe Analog Output Module
- PCIe-5711 (PN: JY5711001-02)
32-ch, 2MS/s/ch, 16-bit PCIe Analog Output Module
- USB-5711 (PN: JY5711001-03)
32-ch, 2MS/s, 16-bit USB Analog Output Module

Accessories

- DIN-68S-01(PN: JA9114029-01)
SCSI 68-pin Terminal board
- TB-68(PN: JY2000068-03)
68-Pin SCSI Shielded I/O Connector Block
- ACL-2016868-1(PN: JY2016868-01)
1M 68pin VHDCI 68M-SCSI68M 100 Ω shielded cable
- ACL-2016868-2(PN: JY2016868-02)
2M 68pin VHDCI 68M-SCSI68M 100 Ω shielded cable

Shanghai Jianyi Technology Co., Ltd.

Address: Room 201, Building 3, NO.300 Fangchun Road, Shanghai.

Post Code: 201203

Tel: 021-5047 5899

Website: www.jytek.com

All Rights Reserved. All specifications are subject to change without further notice.